



AXION DECORATIVE COLOURED WALL AND FLOOR PAINTING & COATING



Technical Data Sheet: *Polycoat Marbluxe Paint* (for decorative coating, screeding and painting)

DESCRIPTION:

Polycoat Marbluxe Paint is a premium, high-build decorative coating, screeding, and painting technology engineered for luxurious, high-end wall and floor surface applications. It is 100% waterproof and anti-slip; it delivers a stunning marble-like finish while providing outstanding durability and surface protection.

Polycoat Marbluxe Paint can be combined with Axion Totalcrete or Tuffcrete cement to deliver enhanced coating thickness, superior mechanical strength, improved safety performance, and premium customized textured finishes. It can also be used alone as a premium decorative finishing paint developed specifically for high-end wall and floor painting applications, delivering that same luxurious marble-like appearance alongside outstanding durability and surface protection.

Axion Polycolour Marbluxe Paint is available in a wide range of vibrant and customized colors, allowing for creative design flexibility suitable for both external and internal use; it offers long-lasting protection and aesthetic appeal across a wide range of residential, commercial, and industrial applications.

ADVANTAGES:

- 100% waterproof and damp-resistant
- Anti-slip surface performance

- High-build coating with enhanced thickness
- Superior mechanical strength
- Excellent adhesion to prepared substrates
- Durable and abrasion resistant
- Resistant to cracking, peeling, and delamination
- Fast Setting
- Full decorative control
- Interior and exterior use

PACKAGING:

- Axion Polycolour Marbluxe Paint is available in 30kg.

AVAILABLE COLOURS:

- White
- Off-White
- Yellow
- Brown
- Black
- Grey
- Neutral

RECOMMENDED SUBSTRATES:

- Concrete Surfaces
- Cement Screeds
- Rendered Walls
- Masonry Blocks
- Polystyrene Boards
- Metal Surfaces
- Gypsum Board Coating Against Water Damage
- Floors

USES:

- Decorative coloured wall and floor coating, screeding and painting (interior/exterior)
- Exposed roof decks
- Warehouse floors.
- Balcony
- Retaining walls
- Drive ways
- Crack treatments
- Pile cap coating (bridges)
- Steel coating
- Polystyrene coating etc.

MIX METHOD:

- Before use, Mix thoroughly.

APPLICATIONS:**1. 100% WATERPROOF WALL COATING**

Product Combo	Polycoat Marbluxe Paint + or Tuffcrete Cement
Mix Ratio	1 bucket of Polycoat Marbluxe Paint (30kg) : 1 bag of tuffcrete Cement (20kg)
Mode of Application	Applied using trowel

**2. 100% WATERPROOF FLOOR COATING**

Product Combo	Polycoat Marbluxe Paint + Totalcrete Cement
Mix Ratio	1 bucket of Polycoat Marbluxe Paint (30kg) : 1 bag of totalcrete Cement (20kg)
Mode of Application	Applied using trowel



After the coating process, apply Axion Polycoat Marbluxe Paint with any cement combination to achieve the desired colour finish.

3. 100% WATERPROOF WALL AND FLOOR PAINTING

Product Combo	Axion Polycoat Marbluxe Paint
Mode of Application	Applied using trowel, roller, or spray depending on finish requirement.



COVERAGE:

Painting: 50 SQM

Coating: 20 SQM

STORAGE:

Store in a dry area out of reach of direct sunlight between 3⁰C and 50⁰C.

CAUTION HEALTH AND SAFETY:

Polycoat Marbluxe Paint is not classified as hazardous material. In case of accidental splashes to the eye, rinse with clean water and seek medical advice. For further information refer to the material safety data sheet. Polycoat Marbluxe Paint is nonflammable.

TECHINICAL ADVICE:

Call RTT Sealant: (+1)416-414-4285, (+1)473-406-5336

Email RTT Sealant: www.axioncanada.com

Prepared by: Axion Construction Solutions Inc.

Preparation date: 24th August 2024

TECHINICAL ADVICE:

Customers are advised to consider the information in this data sheet in the context of how the product will be used, including surfaces and any other products used. The information provided in this data sheet represents our best scientific and practical knowledge. Any advice, information or assistance provided by AXION in relation to its products is given in good faith, however is provided without liability or responsibility. Due to the wide variety of site conditions we are unable to assume liability for any loss that may arise from the use of our products. The user is responsible for checking the suitability of products for their intended use..