



AXION HYDROSHIELD DIRECT SCREED BOND/PUTTY



Technical Data Sheet: *Axion Hydroshield Direct Screed Bond/Putty*

DESCRIPTION:

Axion Hydroshield Direct Screed Bond/Putty is a high-performance polymer-modified bonding and waterproofing compound developed for use in combination with Totalcrete or Tuffcrete Cement. It is formulated to produce 100% waterproof, damp-resistant, and weather-resistant screeding for interior and exterior applications.

The product is supplied as a ready-to-use system and does not require the addition of tile gum, cement, top bond, or any other admixture.

ADVANTAGES:

- 100% Waterproof, Damp-proof & Anti-Fungi
- Longer Life Expectancy
- Does not require any other products for its application like water, tile gum, cement, or other screeding bond.
- Reduces cracking and shrinkage
- Excellent adhesion
- Saves cost

PACKAGING:

- Axion Hydroshield Direct Screed Bond/Putty is available in 30kg.

APPEARANCE:

- Without any combination = Milky
- Combination with Totalcrete cement = Grey Colour
- Combination with Tuffcrete cement = White Colour

RECOMMENDED USES:

- Interior and exterior wall screeding and rendering
- 100% waterproofing in wet areas (bathrooms, kitchens, balconies, terraces)

MIX METHOD:

- *Before use, Mix thoroughly.*

APPLICATIONS:

<i>Product Combo</i>	<i>Axion Hydroshield Direct Screed Bond/Putty + Totalcrete Cement or Tuffcrete Cement</i>
<i>Mix Ratio</i>	<i>1 bucket of Axion Hydroshield Direct Screed Bond (30kg) : 1 bag of totalcrete Cement (20kg) or 1 bag of tuffcrete Cement (20kg)</i>
<i>Mode of Application</i>	<i>Applied using any screeding Tools</i>

Note: Axion Hydroshield Direct Screed Bond/Putty is combined with Totalcrete cement for exterior screeding and with Tuffcrete cement for interior screeding.

COVERAGE:

- 45 – 50 SQM

STORAGE:

Store in a dry area out of reach of direct sunlight between 3⁰C and 50⁰C

CAUTION HEALTH AND SAFETY:

Axion Hydrosshield Direct Screed Bond/Putty is not classified as hazardous material. In case of accidental splashes to the eye, rinse with clean water and seek medical advice. For further information refer to the material safety data sheet. Axion Hydrosshield Direct Screed Bond/Putty is nonflammable.

TECHINICAL ADVICE:

Call RTT Sealant: (+1)416-414-4285, (+1)473-406-5336

Email RTT Sealant: www.axioncanada.com

Prepared by: Axion Construction Solutions Inc.

Preparation date: 24th August 2024

TECHINICAL ADVICE:

Customers are advised to consider the information in this data sheet in the context of how the product will be used, including surfaces and any other products used. The information provided in this data sheet represents our best scientific and practical knowledge. Any advice, information or assistance provided by AXION in relation to its products is given in good faith, however is provided without liability or responsibility. Due to the wide variety of site conditions we are unable to assume liability for any loss that may arise from the use of our products. The user is responsible for checking the suitability of products for their intended use.